

Serial No. 09/468,377
Art Unit No. 2134

LISTING OF CLAIMS

1. (previously presented) A method for securely providing data of a content provider to a user without trusting an internet service provider, wherein the content provider and internet service provider are different entities, said method comprising:

a. generating a first key known only to said content provider;

b. encrypting a second key using said first key and an encryption algorithm requiring a one-time password;

c. storing said encrypted second key on a client machine; and

when said user desires to access said data:

d. decrypting said second encrypted key using said first key; and

e. accessing said data using said second key.

2. (original) A method as recited in claim 1, further comprising the step of transmitting the identity of said client machine to said content provider to authenticate that said user is using said client machine, thereby permitting said data to be accessed only on said client machine.

YO999-558

-2-

Serial No. 09/468,377
Art Unit No. 2134

3. (original) A method as recited in claim 1, wherein said one-time password is a unique user identifier and wherein said one-time password is transmitted out of band.
4. (original) A method as recited in claim 1, wherein said second key is required in an algorithm that generates a session key which is used to decrypt said data.
5. (previously presented) A method for securely providing data of a content provider through an internet service provider to a user without trusting an internet service provider, wherein said content provider and said internet service provider are different entities, said method comprising:
 - a. generating a first key known only to said content provider;
 - b. encrypting a second key using said first key and an encryption algorithm requiring a one-time password and a separate user provided password;
 - c. storing said encrypted second key on a client machine; and
when said user desires to access said data:
 - d. decrypting said second encrypted key using said user provided password; and
 - e. accessing said data using said second key.

YO999-558

-3-

Serial No. 09/468,377

Art Unit No. 2134

6. (original) A method as recited in claim 5, further comprising the step of transmitting the identity of said client machine to said content provider to authenticate that said user is using said client machine, thereby permitting said data to be accessed only on said client machine.

7. (original) A method as recited in claim 5, wherein said one-time password is a unique user identifier and wherein said one-time password is transmitted out of band.

8. (original) A method as recited in claim 5, wherein said second key is required in an algorithm that generates a session key which is used to decrypt said data.

9. (previously presented) In a communications network having at least a content provider node and a plurality of client machines, a method of authenticating a user seeking access to secure data of said content provider, wherein said user accesses said content provider through an internet service provider and wherein said internet service provider and said content provider are different entities, said method comprising:

a. transmitting g^a and the identity of the user of said one client machine to said content provider node, wherein g and a are random numbers and where a is known only

YO999-558

-4-

Serial No. 09/468,377

Art Unit No. 2134

to said client machine, and where g is known to both content provider and said client machine;

b. generating $g^a b$, where b is known only to said content provider node;

c. encrypting $g^a b$ with a one-time password of said user;

d. calculating $g^{a(b)}$ by said client machine using said one-time password to decrypt said encrypted $g^a b$; and

e. transmitting $g^{a(b)}$ to said content provider, whereby said client machine's knowledge of $g^{a(b)}$ authenticates said user to said content provider.

10. (original) A method as recited in claim 9, further comprising the step of transmitting the identity of a particular one of said client machines to said content provider to authenticate that said user is using said client machine, thereby permitting said data to be accessed only on said client machine.

11. (original) A method as recited in claim 9, further comprising the step of performing a method authenticated code on $g^{a(b)}$ at said content provider and transmitting the results of performing said method authenticated code to said client, where said client machine verifies said results to authenticate said content provider.

YO999-558

-5-

Serial No. 09/468,377
Art Unit No. 2134

12. (previously presented) A program storage device readable by a machine, tangibly embodying a program of instructions executable by the machine to perform method steps for securely providing data of a content provider to a user, wherein data is transmitted to said user from said content provider through an internet service provider and wherein said content provider and internet service provider are different entities, said method comprising:

- a. generating a first key known only to said content provider;
- b. encrypting a second key using said first key and an encryption algorithm requiring a one-time password; and
- c. storing said encrypted second key on a client machine;

wherein, when said user desires to access said data:
said second encrypted key is decrypted using said first key; and
said data is accessed using said second key.

13. (previously presented) A program storage device readable by a machine, tangibly embodying a program of instructions executable by the machine to perform method steps for securely providing data of a content provider to a user, wherein data is transmitted to said user from said content provider through an internet service provider and

YO999-558

-6-

Serial No. 09/468,377
Art Unit No. 2134

wherein said content provider and internet service provider are different entities, said method comprising:

- a. generating a first key known only to said content provider;
- b. encrypting a second key using said first key and an encryption algorithm requiring a one-time password and a separate user provided password; and
- c. storing said encrypted second key on a client machine;

wherein, when said user desires to access said data:
said second encrypted key is decrypted using said user provided password; and
said data is accessed using said second key.

14. (previously presented) A program storage device readable by machine, tangibly embodying a program of instructions executable by the machine to perform method steps in a communications network having at least a content provider node and a plurality of client machines, said method steps authenticating a user seeking access to secure data of said content provider, wherein data is transmitted to said user from said content provider through an internet service provider and wherein said content provider and internet service provider are different entities,, said method steps comprising:

YO999-558

-7-

Serial No. 09/468,377
Art Unit No. 2134

- a. transmitting g^a and the identity of the user of said one client machine to said content provider node, wherein g and a are random numbers and where a is known only to said client machine, and where g is known to both content provider and said client machine;
- b. generating g^b , where b is known only to said content provider node;
- c. encrypting g^b with a one-time password of said user;
- d. calculating $g^{(a*b)}$ by said client machine using said one-time password to decrypt said encrypted g^b ; and
- e. transmitting $g^{(a*b)}$ to said content provider, whereby said client machine's knowledge of $g^{(a*b)}$ authenticates said user to said content provider.

15. (previously presented) A computer program product for securely providing data of a content provider to a user without first trusting an internet service provider, wherein data is transmitted to said user from said content provider through an internet service provider and wherein said content provider and internet service provider are different entities, said computer program product comprising:

- a. first instruction means for generating a first key known only to said content provider;

Y0999-558

-8-

Serial No. 09/468,377
Art Unit No. 2134

b. second instruction means for encrypting a second key using said first key and an encryption algorithm requiring a one-time password; and

c. third instructions means for storing said encrypted second key on a client machine;

wherein when said user desires to access said data:
said second encrypted key is decrypted using said first key; and

said data is accessed using said second key.

16. (previously presented) A computer program product for securely providing data of a content provider to a user without trusting an internet service provider, wherein data is transmitted to said user from said content provider through an internet service provider and wherein said content provider and internet service provider are different entities, said computer program product comprising:

a. first instruction means for generating a first key known only to said content provider;

b. second instruction means for encrypting a second key using said first key and an encryption algorithm requiring a one-time password and a separate user provided password; and

c. third instruction means for storing said encrypted second key on a client machine;

wherein when said user desires to access said data:

YO999-558

-9-

Serial No. 09/468,377
Art Unit No. 2134

said second encrypted key is decrypted using said user provided password; and

said data is accessed using said second key.

17. (previously presented) A computer program product for use in a communications network having at least a content provider node and a plurality of client machines, said computer program for authenticating a user seeking access to secure data of said content provider, wherein data is transmitted to said user from said content provider through an internet service provider and wherein said content provider and internet service provider are different entities, said computer program product comprising:

a. transmitting g^a and the identity of the user of said one client machine to said content provider node, wherein g and a are random numbers and where a is known only to said client machine, and where g is known to both content provider and said client machine;

b. generating g^b , where b is known only to said content provider node;

c. encrypting g^b with a one-time password of said user;

d. calculating $g^{(a*b)}$ by said client machine using said one-time password to decrypt said encrypted g^b ; and

Serial No. 09/468,377
Art Unit No. 2134

e. transmitting g^{a*b} to said content provider,
whereby said client machine's knowledge of g^{a*b}
authenticates said user to said content provider.

YO999-558

-11-